



HD 5/11 C

Practical, mobile, versatile: the HD 5/11 C cold water high-pressure cleaner for vertical and horizontal operation. With accessory storage, brass cylinder head and automatic pressure relief.



1 Save energy and time: EASY!Force high-pressure guns and EASY!Lock quick-release locks.

- At last - work without getting tired: the EASY!Force high-pressure gun.
- EASY!Lock quick-release locks: durable and robust. And five times faster than screws.

2 Mobility

- The integrated carrying handle on the front of the machine enable easy loading and convenient transport.
- Push handle can be retracted at the push of a button.

3 Flexibility

- Vertical and horizontal operation possible.
- The wheels are not on in horizontal operation. In this way, the machine offers maximum stability.

4 Quality

- The automatic pressure relief protects the components and extends the service life.
- High-quality brass cylinder head.



HD 5/11 C

- Automatic pressure relief
- For vertical and horizontal operation
- Save energy and time: EASY!Force high-pressure guns and EASY!Lock quick-release locks.

Technical data

Order no.	1.520-972.0	
EAN code	4054278296036	
Current type	Ph / V / Hz	1 / 240 / 50
Flow rate	l/h	500
Working pressure	bar / MPa	110 / 11
Max. pressure	bar / MPa	171 / 17.1
Max. feed temperature	°C	bis zu 60
Connected load	kW	2.1
Weight	kg	24.4
Dimensions (L x W x H)	mm	380 x 360 x 930

Equipment

Spray gun	EASY!Force	
High-pressure Hose	m	10 / DN 6, 250 bar
Spray lance	mm	840
Triple nozzle (0°/25°/40°)	Manual	
ANTI!Twist	-	
Pressure switch-off	■	
Servo control	-	

■



	Order no.	ID	Max. working pressure	Length	Price	Description	
Standard with unions on both sides							
High-pressure hose, 10 m, ID 8, AVS trigger gun connector	1	6.110-031.0	ID 8	315 bar	10 m	10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155° C/315 bar.	▲
High-pressure hose, 15 m, ID 8, AVS trigger gun connector	2	6.110-030.0	ID 8	315 bar	15 m	15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155° C/315 bar.	▲
High-pressure hose, 20 m, ID 8, AVS trigger gun connector	3	6.110-032.0	ID 8	315 bar	20 m	20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155° C/315 bar.	▲
High-pressure hose, 30 m, ID 8, including rotary coupling	4	6.110-014.0	ID 8	315 bar	30 m		▲
High-pressure hose, 15 m, ID 10, 220 bar, extension piece	5	6.110-042.0	ID 10	220 bar	15 m		▲
High-pressure hose, 20 m, DN 10, 220 bar, extension	6	6.110-043.0	ID 10	220 bar	20 m	with union on both sides, M 22 x 1.5 with anti-kink protection. NW 10/155° C/220 bar	▲
High-pressure hose, 25 m, DN 10, extension, not rotatable	7	6.110-044.0	ID 10	220 bar	25 m		▲
Hose assembly premium DN10 22MPa 40m	8	6.110-045.0	ID 10	220 bar	40 m		▲
Hose assembly premium DN12 21MPa 15m	9	6.110-059.0	ID 12	210 bar	15 m	High-pressure hose for water volumes greater than 1,800 l/h. With union on both sides. 2x M 22 x 1.5 with anti-kink protection.	▲
Hose assembly premium DN12 21MPa 40m	10	6.110-060.0	ID 12	210 bar	40 m		▲
Hose assembly TR DN10 22MPa 10m	11	6.110-041.0	ID 10	220 bar	10 m		▲
High-pressure hose, 10 m, ID 6, AVS trigger gun connector	12	6.110-034.0	ID 6	250 bar	10 m	10 m high-pressure hose (M 22 x 1.5) with kink protection.	■
	13	6.110-035.0	ID 6	250 bar	10 m	With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 6/155° C/250 bar.	□
High-pressure hose, 10 m, ID 6, 300 bar, AVS trigger gun connection	14	6.110-056.0	ID 6	300 bar	10 m	With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 6/155° C/300 bar	□
Longlife 400 with unions on both sides							
High-pressure hose Longlife 400, 30 m, ID 8, including rotary coupling	15	6.110-023.0	ID 8	400 bar	30 m	With rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose Longlife 400, 20 m, ID 8, extension	16	6.110-027.0	ID 8	400 bar	20 m	with rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose Longlife 400, 15 m, ID 8, including rotary coupling	17	6.110-029.0	ID 8	400 bar	15 m	With rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose 1.5 m, ID 8, including connectors	18	6.110-024.0	ID 8	400 bar	1.5 m	1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).	□
	19	6.110-069.0	ID 8	400 bar	1.5 m		□
Longlife 400 high-pressure hose, 10 m, DN 8,	20	6.110-038.0	ID 8	400 bar	10 m		□
Food industry version with unions on both sides							
High-pressure hose, 10 m, DN 8, suitable for the food industry, extension piece	21	6.110-051.0	ID 8	250 bar	10 m	10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.	▲

■ □ ▲



		Order no.	ID	Max. working pressure	Length	Price	Description	
High-pressure hose, 20 m, ID 8, suitable for food industry, extension piece	22	6.110-052.0	ID 8	250 bar	20 m		20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.	▲
High-pressure hose, 15 m, ID 6, AVS trigger gun connector 11 mm, suitable for food industry, grey	23	6.110-063.0	ID 6	250 bar	15 m		15 m high-pressure hose (DN 6) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. DN 6/155°C/250 bar.	□
Longlife food design with screw connections at both ends								
High pressure hose food ID 8, 10 m	24	6.110-053.0	ID 8	400 bar	10 m		Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose Longlife 400, 15 m, ID 6, AVS trigger gun connection	25	6.110-054.0	ID 8	400 bar	20 m		Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)	□
Special hoses								
High-pressure hose 1.5 m, ID 8, including connectors, outlet bend	26	6.110-068.0	ID 8	400 bar	1.5 m			□

■ □ ▲

HD 5/11 C


1.520-972.0

KÄRCHER



		Order no.	Flow rate				Price	Description	
Trigger guns									
Extended Easy Press trigger gun	1	4.118-005.0						Extended easy press high-pressure trigger gun for high-pressure hoses with rotating connector.	■
Quick connect									
Quick-fitting pipe union coupler trapezo	2	2.115-000.0							□
Quick-fitting pipe union plug nipple tra	3	2.115-001.0							□

■ □ ▲



	Order no.	Max. working pressure	Length		Price	Description	
Rotating spray lances							
850 mm spray pipe, rotatable	1	4.112-006.0	300 bar	840 mm		850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	■
Nozzle light	2	2.680-002.0		125 mm			□
250 mm lance, non-rotatable	3	4.112-027.0	300 bar	250 mm			□
550 mm lance, non-rotatable	4	4.112-024.0	300 bar	400 mm			□
600 mm spray pipe, rotatable	5	4.112-007.0	300 bar	600 mm		600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
1050 mm spray pipe, rotatable	6	4.112-000.0	300 bar	1050 mm		1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
1550 mm spray pipe, rotatable	7	4.112-018.0	300 bar	1550 mm		1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
2050 mm spray pipe, rotatable	8	4.112-021.0	300 bar	2050 mm		2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
Jet pipe extension TR 1000 mm	9	4.112-048.0	300 bar	1000 mm			□
Double lance							
Double lance 960 mm	10	2.112-016.0	310 bar	960 mm		960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	□
Angular spray lance							
Spray lance for toilets and rain gutters	11	4.112-029.0				Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	□
Flexible spray lance							
Flexible lance 1050 mm	12	4.112-035.0	210 bar	1050 mm		1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	□
Articulated joint TR 20	13	4.112-057.0	300 bar				□
Telescopic spray lance							
Telescopic spray pipe	14	4.112-037.0	225 bar	5400 mm			□
Strap for telescopic spray pipe	15	6.373-987.0				Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible.	□
Gutter cleaner							
Gutter cleaning lance	16	2.112-015.0		960 mm		The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	□
Undercarriage spray lance							
Underbody lance	17	4.112-032.0		700 mm		Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	□
Zusatzhandgriff							
	18	4.321-380.0					□
PowerControl spray lance							
Pressure regulating jet pipe packaged Po	19	4.112-045.0					□

■ □ ▲



		Order no.	Max. working pressure	Nozzle size		Price	Description	
Triple nozzles								
Triple nozzle 038	1	4.117-032.0	300 bar	38			Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For water blasters with injector; low-pressure fan jet for detergent removal and application. Connector M 18x1.5.	■
Dirt Blaster, small								
	2	4.114-020.0	180 bar	40				□
Dirt blaster, large								
Dirt blaster - without changeover function	3	4.114-040.0	300 bar	35			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	□

■ □ ▲



1-4

		Order no.	Nozzle size				Price	Description	
Power nozzle spray angle 15°									
	1	2.113-044.0	38						<input type="checkbox"/>
Power nozzle spray angle 25°									
Power nozzle spray angle 25°	2	2.113-006.0	38					Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.	<input type="checkbox"/>
Power nozzle spray angle 40°									
Power nozzle spray angle 40°	3	2.113-003.0	40					Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	<input type="checkbox"/>
HP nozzle spray angle 0°									
High-pressure nozzle spray angle 0°	4	2.113-001.0	40					High-pressure nozzle with powerful jet for extremely stubborn dirt.	<input type="checkbox"/>

■ □ ▲



		Order no.				Price	Description	
Nozzle union								
Protection part TR only for replacement	1	4.112-011.0						<input type="checkbox"/>
Cleaning agent injector								
Cleaning agent injector for high and low pressure (without nozzles)	2	4.637-032.0					Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	<input type="checkbox"/>
Cleaning agent injector for high pressure (without nozzle)	3	4.637-033.0					Cleaning agent dosage at high pressure 3 - 5 %	<input type="checkbox"/>
Machine-specific nozzle kit with order no. 3.637-170.0								
Nozzle insert trapezoidal thread HD-GER	4	4.769-005.0						<input type="checkbox"/>
Nozzle insert with order no. 3.637-001.0								
Nozzle insert with order no. 3.637-001.0, high pressure for machines up to 1,100 l/h	5	4.769-003.0					Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For water blasters with a water flow rate up to 1100 l/h.	<input type="checkbox"/>
Nozzle insert with order no. 3.637-001, low pressure for devices up to 1,100 l/h	6	4.769-001.0					For low pressure with machines up to 1.100 l/h	<input type="checkbox"/>
Rotary coupling								
Rotary coupling	7	4.111-021.0					Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.	<input type="checkbox"/>
Coupling								
Coupler -2xM22x1.5	8	4.111-037.0					Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m.	<input type="checkbox"/>
Connector								
Nozzle screws / screw socket	9	4.111-022.0					Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.	<input type="checkbox"/>
	10	4.111-038.0						<input type="checkbox"/>
Adapter EASY!Lock								
Adapter 1 M22AG-TR22AG	11	4.111-029.0						<input type="checkbox"/>
Adapter 2 M22IG-TR22AG	12	4.111-030.0						<input type="checkbox"/>
Adapter 3 M22IG-TR22AG	13	4.111-031.0						<input type="checkbox"/>
Adapter M 22 - Swivel	14	4.111-032.0					M22 x 1.5 female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	<input type="checkbox"/>
Adapter 5 TR22IG-M22AG	15	4.111-033.0						<input type="checkbox"/>
Adapter 6 TR22IG-M22AG	16	4.111-034.0						<input type="checkbox"/>
Adapter 7 M18IG-TR20AG	17	4.111-035.0						<input type="checkbox"/>
Adapter 8 TR20IG-M18AG	18	4.111-036.0						<input type="checkbox"/>
ADAPTER for replacement TR22IG-M22AG Er	19	4.111-046.0						<input type="checkbox"/>

■ □ ▲



	Order no.	Max. working pressure	Nozzle size	Diameter	Price	Description	
Pipe cleaning hose, ID 6							
Hose assembly TR pipe cleaning DN6 max.2	1	6.110-046.0	250 bar				<input type="checkbox"/>
Pipe cleaning hose, NW 6, 20 m, 250 bar	2	6.110-008.0	250 bar			The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	<input type="checkbox"/>
Hose assembly TR pipe cleaning DN6 max.2	3	6.110-047.0	250 bar				<input type="checkbox"/>
Hose assembly TR pipe cleaning DN6 14MPa	4	6.110-048.0	140 bar				<input type="checkbox"/>
Pipe cleaning hose, NW 6, 20 m	5	6.110-049.0	140 bar			The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	<input type="checkbox"/>
Pipe cleaning hose, ID 6, 30 m	6	6.110-050.0	140 bar			30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	<input type="checkbox"/>
Pipe cleaning nozzle							
Dirt blaster pipe cleaning D21/040	7	4.765-001.0		40	21 mm		<input type="checkbox"/>
Dirt blaster pipe cleaning D30/040	8	4.765-004.0		40	30 mm		<input type="checkbox"/>
Pipe cleaning nozzle	9	5.763-015.0		55	16 mm	16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	<input type="checkbox"/>
	10	5.763-020.0		65	16 mm		<input type="checkbox"/>
	11	5.763-017.0		50	30 mm	Pipe cleaning nozzle with inner thread. Different spray directions. The hose moves freely through the pipe. (R 1/8" connection, 3 x 30° backwards, diameter 30 mm)	<input type="checkbox"/>
Rotating pipe cleaning nozzle	12	6.415-428.0		50	16 mm	Pipe cleaning nozzle with four rotating jets and inner thread. Different spray directions. The hose moves freely through the pipe. With R 1/8" connection.	<input type="checkbox"/>
Pipe cleaning dirt blaster D 25 / 040	13	6.415-944.0		40	25 mm	The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling.	<input type="checkbox"/>
Pipe cleaning dirt blaster D 30 / 040	14	6.415-946.0		40	30 mm		<input type="checkbox"/>
Pipe cleaning dirt blaster D 35 / 040	15	6.415-948.0		40	35 mm		<input type="checkbox"/>

■ □ ▲



	Order no.	Flow rate	Nozzle size	Diameter	Price	Description	
FR Classic surface cleaner							
FR Classic	1	2.111-016.0		300 mm			<input type="checkbox"/>
Hard Surface Cleaner FRV 30							
Rubber lip for FRV 30	2	2.642-910.0				For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes.	<input type="checkbox"/>
Extension hose 5 m	3	4.440-939.0				5m extension hose for FRV 30. Connection sleeve included.	<input type="checkbox"/>
ABS hose fastening	4	2.642-528.0					<input type="checkbox"/>
ABS dirt trap	5	2.642-532.0					<input type="checkbox"/>
FRV 30 surface cleaner	6	2.111-010.0					<input type="checkbox"/>
Hard surface cleaner FR 30							
FR 30	7	2.111-011.0		300 mm			<input type="checkbox"/>
FR 30 Me surface cleaner							
Hard surface cleaner FR 30 Me	8	2.111-013.0		300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	<input type="checkbox"/>
Machine-specific nozzle kits for FR							
Nozzle kit for surface cleaners	9	2.640-482.0	450-500 l/h			Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (450 to 500 l/h).	<input type="checkbox"/>
Machine-specific nozzle kits for FRV							
Nozzle kit 035 - for FRV 30	10	2.642-430.0		35			<input type="checkbox"/>
Machine-specific nozzle kits for FR Classic							
	11	2.885-313.0		34			<input type="checkbox"/>
FRV 30 Me surface cleaner							
FRV 30 Me extension hose	12	4.441-040.0					<input type="checkbox"/>
FRV 30 Me	13	2.111-012.0					<input type="checkbox"/>

■ □ ▲



		Order no.	Flow rate				Price	Description	
Cup foam lance									
Foam lance TR	1	4.112-053.0	350-600 l/h						<input type="checkbox"/>
Packing complete for 6.394-969.0	2	2.112-018.0							<input type="checkbox"/>
Tank grey only for replacement 1L	3	6.414-050.0							<input type="checkbox"/>
Inno Foam Kit									
Inno Foam Set with detergent injector	4	2.112-000.0						High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	<input type="checkbox"/>
Easy Foam Set									
Easy Foam Set with RM injector	5	2.112-010.0						HP foam system for use with HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	<input type="checkbox"/>
Nozzle kits for Inno/Easy Foam Set									
Nozzle kit 055 for Inno / Easy Set 500-600 l/h	6	2.111-009.0	500-600 l/h					Optimal adaptation to different machine outputs for economic use.	<input type="checkbox"/>
Foam nozzle mounting kit									
Foam nozzle attachment kit	7	2.112-013.0						Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	<input type="checkbox"/>

■ □ ▲



		Order no.	Length			Price	Description	
Automatic, self-winding hose reels								
Automatic hose reel, powder-coated steel / plastic	1	6.392-074.0	20 m				Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	<input type="checkbox"/>
Automatic stainless steel / synthetic material hose drum	2	6.392-083.0	20 m				Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	<input type="checkbox"/>
Automatic hose reel, coated	3	6.392-106.0	20 m				Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	<input type="checkbox"/>
	4	6.392-105.0	20 m					<input type="checkbox"/>
Automatic hose reel, stainless steel, includes swivel holder	5	6.392-076.0	20 m				Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	<input type="checkbox"/>
ABS automatic stainless steel hose drum	6	6.392-122.0	20 m				High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrosion-resistant, watertight, capsuled sprong drive. Connection for HP hoses with nipple.	<input type="checkbox"/>
Add-on kit hose reel TR 40m	7	6.392-442.0	40 m					<input type="checkbox"/>
Powder-coated swivel holder	8	2.639-931.0					Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	<input type="checkbox"/>
ABS pivoting stainless steel wall bracket	9	2.641-867.0					Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	<input type="checkbox"/>

■ □ ▲



		Order no.	Nozzle size			Price	Description	
Wet blasting attachment (without nozzle)								
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0					Paint, rust and scale removal made easy; Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	<input type="checkbox"/>
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0					Paint, rust and scale removal made easy; Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	<input type="checkbox"/>
Nozzle kits for wet jet unit								
Nozzle pack TR wet jet set 0035	3	2.112-021.0	35					<input type="checkbox"/>
Boron carbide nozzle								
Boron carbide nozzle, for machines up to 1,000 l/h	4	6.415-084.0	6 mm				In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	<input type="checkbox"/>

■ □ ▲

HD 5/11 C 1.520-972.0



		Order no.				Price	Description		
Y distributor									
Y distributor	1	4.111-024.0							<input type="checkbox"/>

■ □ ▲



		Order no.	Length	Diameter		Price	Description	
Geka coupling								
Geka connector with hose barb, R 1/2"	1	6.388-461.0					with hose liner	<input type="checkbox"/>
Geka connector with hose barb, R 3/4"	2	6.388-455.0						<input type="checkbox"/>
Geka connector with hose barb, R 1"	3	6.388-465.0						<input type="checkbox"/>
Geka connector with inner thread, R 3/4"	4	6.388-473.0					with female thread	<input type="checkbox"/>
Suction filter								
Water suction filter	5	6.414-956.0						<input type="checkbox"/>
Suction filter with check valve	6	4.730-012.0					Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	<input type="checkbox"/>
Water fine filter								
Water fine filter, with adapter	7	4.730-102.0					Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the water blaster from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	<input type="checkbox"/>
Water supply hose								
Water supply hose	8	4.440-038.0	7.5 m				NW 13 R1" / R 3/4", up to 30 °C	<input type="checkbox"/>
	9	4.440-207.0	7.5 m				NW 19 R1" / R 3/4", up to 85 °C, for pick-up	<input type="checkbox"/>
Backflow check valve								
Backflow preventer	10	2.641-374.0					To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure.- hot water resistant up to 80 °C- tested according to IEC 60335-2-79- integrated leakage protection	<input type="checkbox"/>
Other HP Accessories								
Starting current limiter	11	2.637-495.0					Reduces starting current in single-phase supply and protects line fuse.	<input type="checkbox"/>

■ □ ▲

HD 5/11 C 1.520-972.0

KÄRCHER



		Order no.	Flow rate				Price	Description	
Push-on washing brush									
Push-on wash brush	1	4.762-497.0						The wash brush is fitted directly onto the devices' new dual and triple nozzles using clamping.	<input type="checkbox"/>
Push-on washing brush	2	4.113-001.0						Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.	<input type="checkbox"/>
Rotating washing brush									
Rotating wash brush for < 800 l/h machines, nylon bristles	3	4.113-004.0	500-800 l/h					The rotating wash brush gently removes fine dust and grime from all surfaces. Heat-resistant up to 80°C. (M 18 x 1.5, replaceable brush insert).	<input type="checkbox"/>
Rotating wash brush for < 800 l/h machines, natural hair bristles	4	4.113-003.0	500-800 l/h						<input type="checkbox"/>

■ □ ▲



TEL : 0800 002 056
95 Katere Road, New Plymouth
2/355 Kahikatea Drive, Hamilton
www.pacepower.co.nz